



光强分布数据:(角度°, 光强mcd) C0-180

角度	光强	角度	光强	角度	光强	角度	光强	角度	光强	角度	光强
-90.0	16.82	-58.5	47.35	-27.0	98.84	4.5	305.1	36.0	62.21	67.5	38.72
-88.5	18.24	-57.0	48.08	-25.5	106.5	6.0	272.4	37.5	60.37	69.0	36.84
-87.0	19.97	-55.5	48.91	-24.0	115.4	7.5	245.2	39.0	58.77	70.5	35.13
-85.5	22.03	-54.0	49.73	-22.5	125.6	9.0	219.6	40.5	57.28	72.0	33.12
-84.0	24.00	-52.5	50.46	-21.0	137.3	10.5	196.4	42.0	55.96	73.5	30.97
-82.5	25.83	-51.0	51.40	-19.5	150.9	12.0	177.0	43.5	54.66	75.0	29.07
-81.0	27.61	-49.5	52.52	-18.0	166.5	13.5	160.0	45.0	53.56	76.5	27.29
-79.5	29.42	-48.0	53.51	-16.5	184.7	15.0	145.2	46.5	52.54	78.0	25.42
-78.0	31.16	-46.5	54.67	-15.0	205.8	16.5	132.3	48.0	51.66	79.5	23.48
-76.5	32.79	-45.0	56.25	-13.5	230.8	18.0	121.2	49.5	50.64	81.0	21.53
-75.0	34.43	-43.5	58.07	-12.0	256.0	19.5	111.6	51.0	49.88	82.5	19.73
-73.5	36.03	-42.0	60.00	-10.5	284.1	21.0	103.2	52.5	49.24	84.0	18.10
-72.0	37.72	-40.5	62.15	-9.0	319.2	22.5	96.06	54.0	48.45	85.5	16.65
-70.5	39.50	-39.0	64.17	-7.5	355.9	24.0	89.90	55.5	47.90	87.0	15.37
-69.0	41.04	-37.5	66.69	-6.0	382.5	25.5	84.52	57.0	47.20	88.5	14.28
-67.5	42.46	-36.0	69.62	-4.5	402.4	27.0	79.93	58.5	46.36	90.0	13.39
-66.0	43.61	-34.5	72.95	-3.0	416.4	28.5	75.90	60.0	45.30		
-64.5	44.50	-33.0	76.93	-1.5	411.8	30.0	72.38	61.5	44.24		
-63.0	45.17	-31.5	81.33	0.0	392.8	31.5	69.30	63.0	42.88		
-61.5	45.76	-30.0	86.43	1.5	372.3	33.0	66.61	64.5	41.71		
-60.0	46.63	-28.5	92.18	3.0	341.1	34.5	64.24	66.0	40.42		

电学参数:

工作电流If: 20.00mA 工作电压vf: 1.986V
 反向漏电流Ir: 0.00μA (偏置Vr=5.00V)
 电功率P: 39.72mW

光学参数(CIE A):

平均光强扩散角: ?(25%): 46.7° ?(50%): 24.4° ?(75%): 13.3° ?(50%): 24.4°
 最大光强Imax = 416.6 mcd (C=0.0°,G=-2.8°)
 C0-180平面 Imax = 416.6 mcd (G=-2.8°) Io = 392.8 mcd

LED型号: EZDL3D625-5
 测试人员: Damin
 环境温度: 25.3
 制造厂商: Salens

产品编号: YZD20100721A1
 测试日期: 2010-10-27 LED620
 环境湿度: 65%
 备注: 样品质